

# F005-80 | PRIMEPAPER | MATT 80

UNCOATED PAPER

## PRODUCT SPECIFICATION \*

Weight DIN EN ISO 536	g/m <sup>2</sup>	80	± 2
Thickness DIN EN ISO 534	µm	84	± 2
Opacity min. ISO 2469	%	> 90	

### Printability

Simplex printable

### Printing Technology

- Dry toner systems
- Indigo systems
- Gravure and flexo systems

### Certificates

FSC® Mix Credit (available on request)

## BENEFITS AND PROPERTIES

- › Excellent print results
- › High mechanical strength and dimensional stability
- › High opacity
- › High wet strength
- › Free of optical brighteners
- › Compostable - fulfils the requirements of EN13432
- › Free of harmful substances (REACH conformity)
- › FSC® mix credit (available on request)
- › Produced according to hygiene standard (DIN 15593) and quality standards (ISO 9001:2008; ISO 14001:2004; OHSAS 18001:2007) conformity according; BFR recommendation XXXVI and XXXVI/2 as well as FDA §§ 176.170 and 176.180

## KEY APPLICATIONS

### Label Printing

- › Food packaging
- › Wine, spirits, craft beverages

## PRODUCT STRUCTURE



### Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

\* Modifications reserved.

Version 03/2021

