

F026-60 | PRIMEPAPER | MATT 60

UNCOATED SURFACE-TREATED PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	60	± 2
Thickness DIN EN ISO 534	µm	68	± 2
Opacity min. ISO 2469	%	> 80	

Printability

Simplex printable

Printing Technology

- Inkjet water-based dye
- Inkjet water-based pigment

Certificates

FSC® Mix Credit (available on request)

BENEFITS AND PROPERTIES


- › Excellent print results with gravure and flexo printing
- › High mechanical strength and dimensional stability
- › High opacity
- › High wet strength
- › Free of optical brighteners
- › Free of harmful substances (REACH conformity)
- › FSC® mix credit (available on request)
- › Produced according to hygiene standard (DIN 15593) and quality standards (ISO 9001:2008; ISO 14001:2004; OHSAS 18001:2007) conformity according; BFR recommendation XXXVI and XXXVI/2 as well as FDA §§ 176.170 and 176.180

KEY APPLICATIONS

Label Printing

- › Food packaging
- › Wine, spirits, craft beverages

PRODUCT STRUCTURE



Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2021