

L22274 | ATTRACT FIBRE | MATT 210

SPECIAL-COATED MATT PAPER

LABEL PRINTING

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	207	± 7
Thickness DIN EN ISO 534	µm	322	± 15
	mil	12.7	± 0.6
CIE whiteness (D65/10°) min. ISO 2469		> 78	
Opacity min. ISO 2469	%	> 93	

Printability

Duplex printable

Printing Technology

- ◆ Inkjet water-based dye
- ◆ Inkjet water-based pigment

Certificates



DIN EN ISO 9706

FSC® mix credit (available on request)

BENEFITS AND PROPERTIES


- › Natural, warm tone paper with smooth surface
- › Pin-sharp details
- › Vivid colours
- › High colour consistency and gamut
- › Excellent runability and finishing
- › Meets criteria for permanence according ISO 9706
- › FSC® mix credit (available on request)

KEY APPLICATIONS

Label printing

- › Food packaging: hang-tags
- › Wine, spirits, craft beverages: hang-tags
- › Retail: hang-tags
- › Events: tickets, name badges

PRODUCT STRUCTURE



Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2020

