

L50432 | ATTRACT VELVET | MATT I30

UNCOATED NONWOVEN

LABEL PRINTING

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	135	± 10
Thickness DIN EN ISO 534	µm	225	± 10
	mil	8.9	± 0.4
CIE whiteness (D65/10°) min. ISO 2469		> 97	
Opacity min. ISO 2469	%	> 88	

Printability

Simplex printable

Printing Technology

- Dry toner systems
- Indigo systems
- Inkjet UV systems

Certificates

FSC® mix credit (available on request)

BENEFITS AND PROPERTIES

- › Soft-touch feeling and natural haptics
- › Perfect printability
- › Perfect smudge and water-resistance
- › Excellent runability and finishing
- › High mechanical stability
- › Free of harmful substances
- › FSC® mix credit (available on request)

KEY APPLICATIONS

Label printing

- › Food packaging: honey, marmelade
- › Wine, spirits, craft beverages

PRODUCT STRUCTURE

NONWOVEN BASE



Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2020

