

L80125 | ATTRACT SHINE | EXTRA GLOSSY 95

MICROPOROUS COATED PAPER

LABEL PRINTING

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	95	± 6
Thickness DIN EN ISO 534	µm	106	± 6
	mil	4.2	± 0.2
Gloss BYK (60°) ISO 2813		50	± 7
CIE whiteness (D65/10°) min. ISO 2469		> 136	
Opacity min. ISO 2469	%	> 91	

Printability

Simplex printable

Printing Technology

- 💧 Inkjet water-based dye
- 💧 Inkjet water-based pigment

Certificates

FSC® mix credit (available on request)

BENEFITS AND PROPERTIES

- › Super high gloss surface
- › Pin-sharp details
- › High colour consistency and gamut
- › Excellent runability and finishing
- › Instant dry
- › FSC® mix credit (available on request)

KEY APPLICATIONS

Label printing

- › Home and personal care: cosmetic products
- › Transport and logistics: shipping, barcode, tracking
- › Food packaging
- › Wine, spirits, craft beverages
- › Retail: packaging, shelf marking, coupon, promotions
- › Healthcare and pharmaceuticals: laboratory, nutraceuticals
- › Office: organisation

PRODUCT STRUCTURE



Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Version 03/2020

